



SECTION A-A

NOTES:

1. THIS DRAWING SHOWS REQUIREMENTS FOR PROVIDING MINIMUM CLEAR SPACE AROUND EXISTING OBSTRUCTIONS IN NEW AND EXISTING, NON-STANDARD CURBSIDE SIDEWALK. COMMON OBSTRUCTIONS INCLUDE FIRE HYDRANTS, MAIL BOXES, UTILITY POLES, AND OTHER OBJECTS THAT MAY IMPEDE PEDESTRIAN TRAFFIC.
2. W = MINIMUM SIDEWALK WIDTH. SEE STANDARD DRAWING NO. 313 FOR MINIMUM SIDEWALK WIDTHS AND CONSTRUCTION SPECIFICATIONS. THE ACTUAL AMOUNT OF CLEAR SPACE BETWEEN THE OBSTRUCTION AND BACK OF THE SIDEWALK SHALL EQUAL THE MINIMUM SIDEWALK WIDTH (4.0' MIN. WITH APPROVAL OF THE CITY ENGINEER).
3. FOR UPGRADING EXISTING CURBSIDE SIDEWALK, MIN. LIMITS OF SIDEWALK REPLACEMENT ARE AS SHOWN. CONSTRUCTION OF ADDITIONAL SIDEWALK AGAINST THE BACK OF EXISTING SIDEWALK TO MEET MIN. CLEAR SPACE REQUIREMENTS IS NOT PERMITTED.
4. ADDITIONAL PUBLIC R.O.W. MAY BE REQUIRED TO MEET MINIMUM SIDEWALK WIDTH REQUIREMENTS.
5. THE ENCROACHMENT PERMIT ISSUED FOR A SPECIFIC SITE WILL DETERMINE CONFIGURATION OF SIDEWALK INVOLVING NON-STANDARD DIMENSIONS AND R.O.W. LIMITATIONS.

CITY OF ALBANY, OREGON
PUBLIC WORKS DEPARTMENT

CONSTRUCTION OF SIDEWALK
AROUND EXISTING OBSTRUCTIONS
ON CURBSIDE SIDEWALK

NO SCALE

JUNE 2023

NO. 314